

12

EUROPEAN PATENT APPLICATION

21 Application number: 89309270.0

51 Int. Cl. 5: **H 04 Q 7/04**
H 04 B 7/26

22 Date of filing: 12.09.89

30 Priority: 12.09.88 US 243542 16.12.88 US 285273

43 Date of publication of application:
21.03.90 Bulletin 90/12

84 Designated Contracting States:
AT BE CH DE ES FR GB GR IT LI LU NL SE

71 Applicant: **MOTOROLA INC.**
1303 East Algonquin Road
Schaumburg Illinois 60196 (US)

72 Inventor: **Smith, John M.**
9N556 Nokomis Lane
Elgin Illinois 60123 (US)

Long, James F.
22 W 750 Elmwood Drive
Glen Ellyn Illinois 60137 (US)


Wanat, Ronald J.
868 Arthur Drive
Elgin Illinois 60120 (US)

Kobrinetz, Anthony
4230 Sturbridge Drive
Hoffman Estates Illinois 60195 (US)

74 Representative: **Dunlop, Hugh Christopher et al**
Motorola European Intellectual Property Operations
Jays Close Viabes Industrial Estate
Basingstoke, Hampshire RG22 4PD (GB)

54 High capacity sectorized cellular communication system.

57 A cellular radiotelephone communication system (120, 114, 116 and 118) employs floating/overflow channels (530) to accommodate high traffic sectors. The system includes base site equipment (220) serving an associated cell for communicating with subscriber units in sectorized regions, and a plurality of dynamically assignable floating communication channels (530) for communication between the base site equipment and subscriber units at a sector of a cell.



EP 0 359 535 A2

Description

HIGH CAPACITY SECTORIZED CELLULAR COMMUNICATION SYSTEM

Field of the Invention

The present invention relates generally to radio frequency (RF) communication systems, and, more particularly, to sector-transmit and sector-receive cellular communication systems.

Description of the Prior Art

Mobile radiotelephone service has been in use for some time and traditionally has been characterized by a central site transmitting with high power to a limited number of mobile or portable units in a large geographic area. Mobile or portable transmissions, due to their lower transmission power, were generally received in previous systems by a network of receivers remotely located from the central site and received transmission was subsequently returned to the central site for processing. In previous systems only a limited number of radio channels were available, thus limiting the number of radiotelephone conversations in an entire city to the limited number of channels available.

Modern cellular radiotelephone systems have a comparatively large number of available radio channels which can be effectively multiplied by reuse of the channels in a metropolitan area by dividing the radio coverage area into smaller coverage areas (cells) using low power transmitters and coverage restricted receivers. Such cellular systems are further described in U.S. Patent Numbers 3,906,166, 4,485,486, and 4,549,311, each assigned to the assignee of the present invention.

Some of the more spectrally efficient cellular radiotelephone systems employ center illumination in which each cell is subdivided into sectors. The sectors are illuminated by directional antennas. Each sector is provided with a number of dedicated voice channels. Such a system is described in U.S. Pat. Nos. 4,128,740 and 4,696,027, each assigned to the assignee of the present invention. The sectors are used to substantially eliminate interference from adjacent co-channels.

Unfortunately, the known spectrally efficient cellular radiotelephone systems cannot provide sufficient channel capacity to accommodate the ever-increasing demands of a cellular operation. Consider a relatively large cell wherein each sector covers a large geographic area. An aggregation of subscribers in a given sector can readily occupy every available voice channel available in that sector.

There has, however, been system development to overcome this problem. One particular system, as is described in U.S. Pat. No. 4,144,411, subdivides each cell into subcells which operate simultaneously on independent and noninterfering voice channels. Although this implementation has proven quite useful for increasing channel capacity in each cell, it is rather expensive to implement due to the duplicity of base site equipment that is required.

Further, none of the above discussed techniques accommodate narrow and long communication

paths in which cellular communication is required at low cost and over long and narrow geographic zones, for example, along highways or train tracks.

There is therefore a need for a cellular radiotelephone system which overcomes these deficiencies.

Objects and Summary of the Present Invention

It is a general object of the present invention to provide a cellular radiotelephone system which overcomes the aforementioned deficiencies.

It is a more particular object of the present invention to provide a sectorized cellular radiotelephone system which dynamically assigns voice channels in a cell according to communication demands within each sector and which optimizes the quality and the efficiency of the available channels in a cell.

It is another object of the present invention to provide such a system which provides flexible voice channel assignments along a narrow and long communication path.

The present invention may best be described in terms of a preferred embodiment wherein a cellular radiotelephone communication system employs base site equipment for communicating with subscriber units in a plurality of regions including at least two sectorized regions. The sectorized regions form at least part of a geographic communication area served by the base site equipment. The operation of the base site equipment is controlled by a base site controller which assigns at least one floating communication channel for communication between the base site equipment and a subscriber unit at at least two of the plurality of regions.

In another aspect of the present invention, the base site equipment includes an omni-directional antenna for serving a region which encompasses geographic areas which would otherwise be inaccessible to the subscriber unit. Such an area is illustrated in Fig. 6.

Brief Description of the Drawings

Fig. 1 is a block diagram of a conventional center illuminated sector radiotelephone communication system.

Fig. 2 is a more detailed block diagram of cell site equipment which may be used by the system illustrated in Fig. 1, according to the present invention.

Fig. 3 is diagram of an RF switch employable by the the system illustrated in Fig. 2, according to the present invention.

Figs. 4a, 4b and 4c comprise diagrams of equipment employed at the sectors in the system illustrated in Fig. 2, according to the present invention.

Fig. 5 is flow chart useful for operating the system illustrated in Fig. 2, according to the present invention.

Fig. 6 is a detailed block diagram of cell site

equipment which is similar to the equipment shown in Fig. 2 but modified to accommodate narrow communication regions.

Detailed Description of the Preferred Embodiment

Referring now to Fig. 1, there is illustrated a cellular radiotelephone communications system of the type which may particularly benefit from the invention herein described. Such a cellular communications system is further described in U.S. Patent Numbers 3,663,762, 3,906,166; in an experimental cellular radiotelephone system application with the Federal Communications Commission by Motorola and American Radio-Telephone Service, Inc., in February 1977; and more recently in a system described entitled "Motorola DYNATAC Cellular Radiotelephone System", published by Motorola, Inc., Schaumburg, Illinois in 1982. Such cellular systems provide telephone coverage to both mobile and portable radiotelephones located throughout a large geographical area. Portable radiotelephones may be of the type described in U.S. Patent Numbers 4,486,624; 3,962,553; and 3,906,166 and each assigned to the assignee of the present invention; and mobile radiotelephones may be of the type described in Motorola instruction manual number 68P81039E25, published by Motorola Service Publications, Schaumburg, Illinois in 1979. Although the present invention will be described with particularity for the center illuminated sector cell system, it is obvious that a person skilled in the art may be able to apply the essence of the present invention to other types of sectorized cellular configurations.

As illustrated in Fig. 1, the geographical area is subdivided into cells 102, 104 and 106 which are illuminated with radio frequency energy from fixed site transceivers 108, 110, and 112, respectively. The fixed site transceivers may be controlled by base site controllers 114, 116 and 118 as illustrated. These base site controllers are each coupled by data and voice links to a radiotelephone control terminal 120 which may be similar to the terminals described in U.S. Patent Numbers 3,663,762; 3,764,915; 3,819,872; 3,906,166; and 4,268,722. These data and voice links may be provided by dedicated wire lines, pulse code modulated carrier lines, microwave radio channels, or other suitable communication links. Control terminal 120 is, in turn, coupled to the switched telephone network via a conventional telephone central office 122 for completing calls between mobile and portable radiotelephones and landline telephones.

For a more detail discussion of the system illustrated in Fig. 1, reference may be made to U.S. Pat. No. 4,696,027, *supra*.

In one implementation of the present invention realizing sectorized cells, the radio transceivers are connected to the sector antennas as shown in Fig. 2. Each sector antenna is fed by a multicoupler (for example, RX multicoupler 202) to the primary transceiver equipment dedicated to the particular sector (for example, transceiver 204) and to both the adjacent sector transceivers equipment (for example, transceivers 206 for sector 6 and transcei-

vers 208 for sectors 2). The transceivers 204, 206 or 208 provide communication for voice channels which are indicated for use at the associated sector. In addition, each sector antenna is coupled to a signalling receiver allowing the signalling receiver to have access to all six sector antennas. The transmitters (e.g., transmitter 212) of the primary transceiver equipment are coupled to the sector antennas, via respective combiners 282, and duplexers (such as duplexer 210). The duplexers may be similar to model ACD-2802-AAMO manufactured by Antenna Specialists Co., Cleveland, Ohio. The combiners 282 may be implemented using SRF4006B, available from Motorola, Inc., 1501 W. Shure Drive, Arlington Heights, Illinois.

A base site controller 220 is used to control a 6-way switch 230 which couples a floating voice channel transceiver 240 to each duplexer 210, via combiner 282. The transceiver 240 is referred to as a floating voice channel transceiver because it provides, in accordance with the present invention, a voice channel which can float between sectors as channel requests are made in each sector. The receiver portion of the transceiver 240 is interconnected (interconnection not shown) with the receiver multicouplers 202 in the same manner as is illustrated for the transceivers 204, 206 and 208.

This floating implementation is particularly advantageous for rural cellular radiotelephone applications wherein each geographical region covered by an individual sector can be extended beyond typical coverage areas. Consider, for example, a cellular system, according to the present invention, that is designed to cover a large rural geographical area. Each sectorized cell would include a plurality of high gain sectorized antennas, each capable of transmitting at significantly greater radiated power levels than present implementation, e.g., at 500 Watts rather than at current levels approximating 100 Watts. Such increases in transmit power can cost effectively be accomplished by employing conventional high gain sectorized antennas. The signalling channel in the inventive system, as well as in a conventional sectorized cell system, employs an omni-directional antenna. Since the gain of the omni-directional antenna is lower than the gain of a sector antenna, a higher power amplifier is required for the signalling channel in order to match the effective radiated power levels for each type of channel.

A preferred implementation of a floating voice channel system is described with reference to Figs. 3, 4a, 4b and 4c. Figure 3 includes a diagram of a floating voice channel targeted for one of six sectors of a cell. Figure 3 includes a conventional internally terminated RF coaxial switch 310, such as the 6-IT-2L31 available from DB products, Pasadena, California, which switch is used in a manner similar to the switch 230 of Fig. 2. This preferred implementation differs from the implementation of Fig. 2 in that the system employs a plurality of floating voice channels rather than only one floating voice channel. The switch 310 of Fig. 3 is a representative switch for one voice channel (one such switch is utilized for each floating voice channel) that allows the base site

controller to dynamically switch the one associated voice channel to any particular sector.

Such dynamic switching is useful, for example, when a subscriber transits from one sector to another. In this instance, the base site controller needs only to switch a floating voice channel assigned to the subscriber to the next sector. More importantly, as previously discussed, this dynamic switching provides significant improvement to the system in that each available floating voice channel can be switched to any sector to service an influx of subscribers demanding service thereat. The availability of a single floating channel provides a channel capacity increase for every sector in a cell. At least in part, because radiotelephone calls are relatively brief and because communication systems can be designed such that a request for an additional communication channel in a particular geographic region is unlikely, the effective channel capacity improvement is significantly greater than what would otherwise be achieved by adding additional fixed channels in each sector. For example, the effective channel capacity improvement is illustrated by comparing two cells providing substantially identical traffic density characteristics (e.g., using conventional Erlang unit measurements). The first cell is a conventional cell having 6 sectors with 3 dedicated channels per sector and having no floating channels, and the second cell is a cell, designed in accordance with the present invention, having 6 sectors with 1 dedicated channel per sector and having 5 floating channels employable within the cell. It is readily apparent that 18 channels are required for the conventional implementation, while only 11 channels are required for the inventive implementation.

For a statistical analysis on the practicability of "overflow" channels in a general communication system, reference may be made to "Practical Traffic Engineering of Least Cost Routing Systems - Part 5, 'Peaked' Traffic: What It Is and When You Should Worry About It", Michael T. Hills, Business Communications Review, July-August, 1983.

One skilled in the art will recognize the need to avoid co-channel interference between sectorized regions. For example, it is useful to avoid such interference by employing floating channels that have ample reuse distance. The orientation of the dedicated channels is preferably designed as is illustrated and described in U.S. Pat. No. 4,128,740, assigned to the assignee of the present invention.

One skilled in the art will further recognize that any number of dedicated channels per sector may be employed and that any number of floating channels per cell may be employed without departing from the scope of the present invention. For example, it may be desirable to employ zero dedicated channels per sector and a plurality of floating channels per cell.

In Fig. 4a, a general block diagram of the floating voice channel interconnection is illustrated for sector 1 of a representative cell. A voice channel transmitter 450 is shown coupling a sector dedicated (or fixed) voice channel, i.e., a voice channel which does not float, to a conventional channel combiner 455. Also intercoupled to the combiner 455 are signal paths 460, 462, 464 and 466 for

respectively carrying four floating voice channels from an RF coaxial switch 310. The combiner 455 operates conventionally to intercouple the voice channels (paths) to the sector's antenna 458.

Fig. 4b illustrates a general block diagram of the equipment for sector 2 of the representative cell, which equipment is essentially identical to the equipment illustrated in Fig. 4a. In Fig. 4b, a voice channel transmitter 470 is shown coupling another sector dedicated voice channel to a similar channel combiner 475. Coupled to an antenna 478, via the combiner 475, are signal paths 480, 482, 484 and 486 for respectively carrying the same four floating voice channels from another RF coaxial switch 310 dedicated for use at sector 2 of the representative cell.

In more detail than the block diagram of Figs. 4a and 4b and consistent with the equipment of Fig. 2, Fig. 4c illustrates a block diagram of equipment for a representative sector for such an inventive system. Included therein are blocks representative of those illustrated in Fig. 2: base site controller 220, (voice channel) transceiver 240, switch 230, transceivers 204, duplexer 210, receiver multicoupler 202, and 5 channel combiner 282, representative of the combiner 455 or 475 of Figs. 4a and 4b. The combiner 282 is illustrated combining the outputs of the switch 230, the other switches (not shown) and the outputs of transceivers (transmitters) 204 to the duplexer 210. Other interconnections are consistent with the illustration of Fig. 2.

Fig. 6 illustrates cell site equipment substantially the same as in Fig. 2 but including modifications to accommodate narrow communication regions, for example, along highways. The equipment that is common to the equipment in both Figs. 2 and 6 should be apparent from the common terminology used therein. Differences between the Figs. 2 and 6 include the omission of cell site equipment associated with antenna sectors 2, 3, 5 and 6; the addition of a conventional omni-directional antenna 612; and the associated cell site equipment for the omni-antenna zone 614 (depicted in dotted lines about the omni-antenna 612).

This arrangement of Fig. 6 is preferably used in a manner substantially similar to the operation of the cell site equipment of Fig. 2. At least one floating voice channel is provided through the switch 230 for communication in one of the three regions, i.e., one of the two sectorized regions or the omni-antenna zone (region). Upon demand, the floating voice channel is switched to the region requesting service. This manner of operation is particularly useful in a rural highway or railway application whereat the sectorized regions are aligned to cover as long a portion of the traveled path as possible.

In either situation, the traveling subscriber enters the communication system coverage area at one of the two sectorized regions and is assigned either a fixed channel or a floating channel. If the floating channel is assigned, the floating channel is preferably used throughout the path of travel, e.g., from antenna sector region 1, to the omni zone and into the antenna sector region 4. If a fixed channel is originally assigned, the floating channel is preferably

used once the subscriber enters the omni-zone and, thereafter, used throughout the path of travel.

This arrangement of Fig. 6 provides significant advantages. The omni-zone prevents calls from being dropped as a subscriber rapidly crosses the sectorized regions. The omni-zone allows communication to be maintained while the subscriber is physically beneath the communication path of the sector antennas. Additionally, this arrangement provides an extremely cost effective implementation for this type of application. The floating channel technique reduces the cost by eliminating the need for equipment to accommodate unused channels.

Fig. 5 illustrates a flow chart useful for operating channel assignments in a particular cell for the system illustrated in Fig. 2, according to the present invention. This flow chart accommodates assignment operation for both floating voice channels as well as fixed (dedicated) voice channels for a cell. Modification of this flow chart for the operation of the equipment arranged in Fig. 6 should be readily apparent. The flow chart begins at block 510 where the base site controller is depicted monitoring the signalling channel for a subscriber radiotelephone call request. From block 510, flow proceeds to block 515 where a test is performed by the base site controller to determine if a subscriber station has requested the use of the voice channel in a sector. If not, flow proceeds to block 510.

If a subscriber station has requested a voice channel in a particular sector, flow proceeds from block 515 to block 520 where another test is performed to determine if a fixed channel is available in the particular sector. If a fixed channel is available, flow proceeds to block 525 where a channel assignment is made to the available voice channel. From block 525, flow returns to block 510.

If a fixed channel is not available in a particular sector, flow proceeds from block 520 to block 530 where a test is performed to determine if a floating channel is available in a particular sector. If a floating channel is available, flow proceeds to block 535 where the base site controller (BSC) controls the sector's RF coaxial switch to connect the available floating channel to the requesting subscriber station. From block 535, flow proceeds to block 540 where the actual channel assignment is made. Once the radiotelephone call terminates on the floating channel, depicted by block 540, the base site controller disconnects the connection of the floating channel to the particular sector, depicted at block 550. From block 550, flow returns to block 510.

From block 530, if a floating channel is not available in the particular sector, flow proceeds to block 560 where a test is performed to determine if a fixed channel is available in a sector which is adjacent to the particular sector in which a subscriber station requests a channel. This test illustrated in block 560 is typical (often referred to as sector sharing) in conventional sectorized telephone communication systems when there are no voice channels available at the sector from which a channel is requested. Thus, if a fixed channel is available in an adjacent sector, flow proceeds to block 565 where the requesting subscriber station is

assigned a channel from the adjacent sector. From block 565, flow returns to block 510.

If a fixed channel is not available in an adjacent sector, flow proceeds from block 560 to block 570 where the base site controller determines if the requesting subscriber can be assigned to a channel in an adjacent cell, preferably to the nearest sector in the nearest cell, with respect to the subscriber unit. This is conventionally accomplished by determining if the assignment of a channel from an adjacent cell would cause undue cochannel interference in another cell. More specifically, if the subscriber signal strength in the target cell exceeds the system's cochannel interference threshold, flow proceeds to block 580 where the call request is denied (blocked). If the subscriber signal strength is not above the threshold, flow proceeds from block 570 to block 575 where the call is assigned to the adjacent cell. From block 575, flow returns to block 510.

If the signal strength of the requesting subscriber station is above the cochannel interference threshold, flow proceeds from block 570 to block 580 where the base site controller informs the subscriber station that the call request cannot be served. From block 580, flow returns to block 510.

The foregoing sequence illustrated in the flow chart of Fig. 5 incorporates a preferred sequence of channel availability checking. The base site controller first checks if the fixed channel is available in the particular sector, and if not, proceeds to check if a floating channel is available. After the base site controller has determined that neither a fixed nor a floating channel is available in a particular sector, only then does the base site controller check for channel availability in adjacent sectors. This sequence is important for channel usage efficiency. Optimally, the fixed channel(s) in each sector is (are) utilized before any floating channel is utilized.

One skilled in the art will recognized that various modifications may be made to the above described system without departing from the spirit or scope of the present invention.

Claims

1. A cellular radiotelephone communication system, characterized by:

base site equipment (220, 230 & 240) serving an associated cell for communicating with subscriber units in a plurality of sectorized regions (1-6), said sectorized regions composing a geographic communication area for said associated cell; and

means for assigning (230) at least one floating communication channel (240) for communication between the base site equipment and a subscriber unit at at least two of said plurality of said sectorized regions.

2. A cellular radiotelephone communication system according to claim 1, characterized by: means for providing at least one dedicated communication channel (206/208) for communication between the base site equipment and a subscriber unit within each sectorized

region.

3. A cellular radiotelephone communication system according to claim 2, characterized by: processing means (220) for prioritizing the assignment of one of said at least one dedicated communication channels before one of said at least one floating channels for communication in said sectorized regions.

4. A cellular radiotelephone communication system, according to claim 1, further comprising:

control means for intercoupling said base site equipment with a telephone central office; transmission means for transmitting at least one dedicated frequency from the base site equipment to a subscriber unit within each sectorized region;

means for providing a floating frequency (240) transmittable from said base site equipment;

switch means (230) for switching said floating frequency to said transmission means for transmission of said floating frequency in at least two of said sectorized regions;

means, coupled to said base site equipment, for receiving communication from subscriber units on frequencies associated with said at least one dedicated frequency and said floating frequency;

means, coupled to said base site equipment, for prioritizing the assignment of one of said at least one dedicated communication channel before one of said at least one floating channel in a sector; and

means, responsive to channel requests in said sectorized regions, for assigning said at least one dedicated frequency before assigning said floating frequency to a subscriber unit.

5. A cellular radiotelephone communications system according to any one of the preceding claims, further comprising means (560) for assigning a dedicated communication channel of a less preferred sectorized region (206, 208) if the dedicated communication channel of said preferred sectorized region (204) and said at least one floating communication channel (240) are busy.

6. A cellular radiotelephone system according to claim 5 wherein the less preferred sectorized region (206, 208) is adjacent to the dedicated communication channel of said preferred sectorized region (204).

7. A cellular radiotelephone communications system according to any one of the preceding claims further comprising means for causing base site equipment of another cell to assign a communication channel for communication with the subscriber unit if neither the dedicated communication channel of a preferred sectorized region nor of a sectorized region adjacent thereto, nor said at least one floating communication channel is available for communication.

8. A cellular radiotelephone communication system, according to any one of the preceding claims wherein the base site equipment further

includes an omni-directional antenna for serving an associated communication region which is also at least part of the geographic communication area served by said base site equipment.

9. A method of assigning communication channels in a cellular radiotelephone communication system, characterized by:


providing, within an associated cell, base site equipment (220, 230 & 240) that communicates with subscriber units in a plurality of sectorized regions (1-5), said sectorized regions composing said associated cell;

providing at least one floating communication channel (240) for communication between the base site equipment and a subscriber unit that is dynamically assignable (230) at a plurality of said sectorized regions;

and in response to a communication channel request, assigning one of said at least one floating communication channels in one of said sectorized regions.

10. A method according to claim 9 comprising the further step of:

prioritizing the assignment of one of said at least one dedicated communication channel before one of said at least one floating channel in a sector.



— PRIOR ART —

FIG. 1







FIG. 2





FLOATING VOICE CHANNEL BLOCK DIAGRAM**FIG. 4C**

FIG. 5




FIG. 6



Europäisches Patentamt
European Patent Office
Office européen des brevets



Publication number: **0 359 535 A3**

12

EUROPEAN PATENT APPLICATION

21 Application number: 89309270.0

51 Int. Cl.⁵: **H04Q 7/04**, **H04B 7/26**

22 Date of filing: **12.09.89**

30 Priority: **12.09.88 US 243542**
16.12.88 US 285273

43 Date of publication of application:
21.03.90 Bulletin 90/12

84 Designated Contracting States:
AT BE CH DE ES FR GB GR IT LI LU NL SE

66 Date of deferred publication of the search report:
21.11.91 Bulletin 91/47

71 Applicant: **MOTOROLA INC.**
1303 East Algonquin Road
Schaumburg Illinois 60196(US)

72 Inventor: **Smith, John M.**
9N556 Nokomis Lane
Elgin Illinois 60123(US)
Inventor: **Long, James F.**
22 W 750 Elmwood Drive
Glen Ellyn Illinois 60137(US)
Inventor: **Wanat, Ronald J.**
868 Arthur Drive
Elgin Illinois 60120(US)
Inventor: **Kobrinetz, Anthony**
4230 Sturbridge Drive
Hoffman Estates Illinois 60195(US)

74 Representative: **Dunlop, Hugh Christopher et al**
Motorola European Intellectual Property
Operations Jays Close Viabes Industrial
Estate
Basingstoke, Hampshire RG22 4PD(GB)

54 **High capacity sectorized cellular communication system.**

57 A cellular radiotelephone communication system (120, 114, 116 and 118) employs floating/overflow channels (530) to accommodate high traffic sectors. The system includes base site equipment (220) serving an associated cell for communicating with

subscriber units in sectorized regions, and a plurality of dynamically assignable floating communication channels (530) for communication between the base site equipment and subscriber units at a sector of a cell.

EP 0 359 535 A3




FIG. 2



European
Patent Office

EUROPEAN SEARCH REPORT

Application Number

EP 89 30 9270

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
X	US-A-4 144 496 (CUNNINGHAM et al.) * Column 1, lines 9-15; column 2, lines 24-30,41-47; column 4, lines 21-26; column 5, lines 26-55; column 6, lines 30-48; column 12, line 50 - column 13, line 31; column 14, lines 24-68 *	1-4,8-10	H 04 Q 7/04 H 04 B 7/26
X	INTERNATIONAL SWITCHING SYMPOSIUM 1987, "Innovations in Switching Technology", Phoenix, Arizona, 15th - 20th March 1987, pages 753-758; B. EKLUNDH et al.: "Load sharing in a cellular mobile telephone system bloc- king probabilities and channel utilization" * Page 753, right-hand column, lines 22-39; page 754, left-hand column, lines 53-60 *	1-4,9,10	
A	IDEM	5-7	
A	GB-A-2 173 377 (INTERNATIONAL STANDARD ELEC- TRIC) * Page 1, line 64 - page 2, line 4; page 2, lines 16-28; page 3, lines 47-56 *	1,2,5-7	
A	37TH IEEE VEHICULAR TECHNOLOGY CONFERENCE, Tampa, Florida, 1st - 3rd June 1987, pages 405-411; K. SALLBERG et al.: "Hybrid channel assignment and reuse partitioning in a cellular mobile telephone system" * Page 406, left-hand column, lines 20-60 *	1-7,9,10	TECHNICAL FIELDS SEARCHED (Int. Cl.5) H 04 Q
A,D	MOTOROLA: "Overview of DYNA T.A.C Cellular Radiotele- phone Systems", 4th edition, May 1984, Schaumburg, US * Chapter 4.2: "Sector sharing" *	1,5-7	
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of search 06 September 91	Examiner BEHRINGER L.V.
<div>CATEGORY OF CITED DOCUMENTS</div> <div>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document T: theory or principle underlying the invention</div> <div>E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document</div>			